

| Tuna of luminaira                        | commercia  | I track light   |
|--|------------|---|
| Type of luminaire commercial track light |            |   |
| Set model No.                            | AL-TL0128- |   |
| Image photo                              |            | Dimension and materials   |
|  |            | 80<br>80<br>80<br>80<br>80<br>80<br>80<br>80<br>80<br>80<br>80<br>80<br>80<br>8 |
| Type of light source                     | CREE 1820  | Lamp diameter 83.5mm  |
| Dimming                                  | _          | Weight 1.4KG  |
| Dimming range                            |            | Body Aluminium  |
| Power input                              | 28W        | Reflector Aluminium   |
| Power voltage                            | 220V       | Photometric chart   |
| Input frequency                          | 50/60Hz    | Illumination Cone Curve   |
| Driver                                   | Integrated | H[m] Diameter[m] Illuminance[ts]  |
| IP rating                                | IP20       | 18325.48<br>1.6 4881.37<br>4881.37  |
| Beam angle                               | 28°        | 2.4 2036.16<br>2096.16  |
| System lumen out put                     | 2560 lm    | 3.2<br>1145.34<br>1145.34<br>4.0 733.02   |
| System efficacy                          | 90 lm/W    | 733.02 CO-C180  |
| ССТ                                      | 4000K      | Distribution Curve of Meridian  -150  -150  150                                 |
| CRI                                      | 80         | -120  |
| Life time                                | 50000      | -90   |
| Brand                                    | ALIGHT     | -60 -30 Unit: cd 0 - c0 /180  |
| Country of origin                        | China      | — c30/210<br>— c30/210<br>— c60/240<br>— c90/270                                |
| Remarks                                  |            |   |