




ALIGHT

COB LED Solution Company Since 2008

Type of luminaire		<i>commercial track light</i>																																	
Set model No.		<i>AL-TL0612-L</i>																																	
Image photo		Dimension and materials																																	
																																			
Type of light source	<i>CREE 1507</i>	Lamp diameter <i>75mm</i>																																	
Dimming	—	Weight <i>1.1KG</i>																																	
Dimming range		Body <i>Aluminium</i>																																	
Power input	<i>12W</i>	Reflector <i>Aluminium</i>																																	
Power voltage	<i>220V</i>	Photometric chart																																	
Input frequency	<i>50/60Hz</i>	<p style="text-align: center;">Illumination Cone Curve</p> <table border="1"> <thead> <tr> <th>H[m]</th> <th>Diameter[m]</th> <th>Illuminance[lx]</th> </tr> </thead> <tbody> <tr> <td>0.8</td> <td></td> <td>2729.84</td> </tr> <tr> <td></td> <td></td> <td>2719.34</td> </tr> <tr> <td>1.6</td> <td></td> <td>682.46</td> </tr> <tr> <td></td> <td></td> <td>679.84</td> </tr> <tr> <td>2.4</td> <td></td> <td>303.32</td> </tr> <tr> <td></td> <td></td> <td>302.15</td> </tr> <tr> <td>3.2</td> <td></td> <td>170.62</td> </tr> <tr> <td></td> <td></td> <td>169.96</td> </tr> <tr> <td>4.0</td> <td></td> <td>109.19</td> </tr> <tr> <td></td> <td></td> <td>108.77</td> </tr> </tbody> </table> <p style="text-align: center;"> ■ C0-C180 ■ C90-C270 </p> <p style="text-align: center;">Distribution Curve of Meridian</p>  <p style="text-align: right;">Unit: cd</p> <ul style="list-style-type: none"> — e0/180 — e30/210 — e60/240 — e90/270 	H[m]	Diameter[m]	Illuminance[lx]	0.8		2729.84			2719.34	1.6		682.46			679.84	2.4		303.32			302.15	3.2		170.62			169.96	4.0		109.19			108.77
H[m]	Diameter[m]		Illuminance[lx]																																
0.8			2729.84																																
			2719.34																																
1.6			682.46																																
			679.84																																
2.4			303.32																																
			302.15																																
3.2			170.62																																
			169.96																																
4.0			109.19																																
			108.77																																
Driver	<i>Integrated</i>																																		
IP rating	<i>IP20</i>																																		
Beam angle	<i>43.2°</i>																																		
System lumen out put	<i>1127 lm</i>																																		
System efficacy	<i>90 lm/W</i>																																		
CCT	<i>2700K-6500K</i>																																		
CRI	<i>80</i>																																		
Life time	<i>50000</i>																																		
Brand	<i>ALIGHT</i>																																		
Country of origin	<i>China</i>																																		
Remarks																																			