







ALIGHT

COB LED Solution Company Since 2008

Type of luminaire		<i>commercial track light</i>																																	
Set model No.		<i>AL-TL0628-60</i>																																	
Image photo		Dimension and materials																																	
																																			
Type of light source	<i>CREE 1820</i>	Lamp diameter <i>75mm</i>																																	
Dimming	—	Weight <i>1.1KG</i>																																	
Dimming range		Body <i>Aluminium</i>																																	
Power input	<i>28W</i>	Reflector <i>Aluminium</i>																																	
Power voltage	<i>220V</i>	Photometric chart																																	
Input frequency	<i>50/60Hz</i>	<p style="text-align: center;">Illumination Cone Curve</p>  <table border="1"> <thead> <tr> <th>H[m]</th> <th>Diameter[m]</th> <th>Illuminance[lx]</th> </tr> </thead> <tbody> <tr><td>0.8</td><td></td><td>4625.86</td></tr> <tr><td></td><td></td><td>4569.97</td></tr> <tr><td>1.6</td><td></td><td>1156.46</td></tr> <tr><td></td><td></td><td>1142.49</td></tr> <tr><td>2.4</td><td></td><td>513.98</td></tr> <tr><td></td><td></td><td>507.77</td></tr> <tr><td>3.2</td><td></td><td>289.12</td></tr> <tr><td></td><td></td><td>285.62</td></tr> <tr><td>4.0</td><td></td><td>185.03</td></tr> <tr><td></td><td></td><td>182.80</td></tr> </tbody> </table> <p style="text-align: center;">Distribution Curve of Meridian</p>  <p style="text-align: center;">Unit: cd — c0/180 — c30/210 — c60/240 — c90/270</p>	H[m]	Diameter[m]	Illuminance[lx]	0.8		4625.86			4569.97	1.6		1156.46			1142.49	2.4		513.98			507.77	3.2		289.12			285.62	4.0		185.03			182.80
H[m]	Diameter[m]		Illuminance[lx]																																
0.8			4625.86																																
			4569.97																																
1.6			1156.46																																
			1142.49																																
2.4			513.98																																
			507.77																																
3.2			289.12																																
			285.62																																
4.0		185.03																																	
		182.80																																	
Driver	<i>Integrated</i>																																		
IP rating	<i>IP20</i>																																		
Beam angle	<i>60°</i>																																		
System lumen out put	<i>2646 lm</i>																																		
System efficacy	<i>90 lm/W</i>																																		
CCT	<i>2700K-6500K</i>																																		
CRI	<i>80</i>																																		
Life time	<i>50000</i>																																		
Brand	<i>ALIGHT</i>																																		
Country of origin	<i>China</i>																																		

Remarks